WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57535
Rec. 5/31 1955
Well No.
Permit No.
Do not fill in

Owner Patrick Keenan Driller Nevada Pump & Supply Co.
Address 85 BMP Road, Henderson, Nevada Address Las Vegas, Nevada Lic. No. 133
Location of well: SE¼ NW¼ Sec. 28, T. 22 N/S, R. 61 E, in Clark County
or
Water will be used for Domestic Total depth of well 120 feet
Size of drilled hole 10" Weight of casing per linear foot 9 lbs.
Thickness of casing 10 gauge Temp. of water
Diameter and length of casing 6" x 120'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure
If nonflowing well give depth of standing water from surface 88 feet
If flowing well describe control works
(Type and size of valve, etc.)
Date of commencement of well May 7, 1955 Date of completion of well May 10, 1955
Type of well rig Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Top Soil
2	6	4	Gravel
6	12	6	Caliche
12	48	36	Sandstone
48	96	48	Hard Sandstone
96	97	1	Loose Sand-Water Bearing
97	113	16	Hard Limestone
113	116	3	Gravel-Water Bearing
116	120	4	Hard Limestone

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 113 to 116 ft.
Other aquifers 96 - 97

First water at 96 feet.

Casing perforated
from 80 to 120 ft.

Size of perforations
1/16" x 6"

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0	120	120	50 feet cement grout 70 feet washed pea gravel fill

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

15 gpm at 115 feet pumping level

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed NEVADA PUMP & SUPPLY COMPANY
Well Driller

By Thos. deBruyn Dr

License No. 133

Dated May 16, 19 55

(Not to be filled in by Driller)