

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. <u>5754A</u>	
Rec. <u>5/31</u> 19	
Well No. ....	
Permit No. ....	
<i>Do not fill in</i>	

Owner John C. Lopez Driller Nevada Pump & Supply Co.

Address 801 N. A Street, Las Vegas, Nev. Address Las Vegas, Nevada Lic. No. 133

Location of well: SE 1/4 NW 1/4 Sec 28., T.22 N/S, R.61 E. in Clark County

or .....

Water will be used for Domestic Total depth of well 150 feet

Size of drilled hole 10" Weight of casing per linear foot 9 lbs.

Thickness of casing 10 gauge Temp. of water .....

Diameter and length of casing 6" x 150'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface 93 feet

If flowing well describe control works .....

(Type and size of valve, etc.)

Date of commencement of well May 11, 1955 Date of completion of well May 12, 1955

Type of well rig Cable Tools

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Top Soil
2	6	4	Gravel
6	12	6	Caliche
12	48	36	Sandstone
48	96	48	Hard Sandstone
96	97	1	Sand-Water Bearing
97	113	16	Hard Limestone
113	120	7	Gravel
120	137	17	Blue Maltipi
137	139	2	Gravel-Water Bearing
139	147	8	Hard White Lime
147	150	3	Very Hard Brown Lime

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)

from 137 to 139 ft.

Other aquifers 96 - 97

---

First water at 96 feet.

Casing perforated

from 90 to 150 ft.

Size of perforations

1/16" x 6"



