WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57578
Rec. 19
Well No. .....
Permit No. .....
Do not fill in

Owner: Gilbert Tafoya Driller: Joseph E. Metz
Address: Lot #8 Bk #1 Happy Valley Ranchos Address: N. Las Vegas Lic. No. 35
Location of well: ¼ NE ¼ Sec. 29, T. 20 N/S, R. 62 E, in Clark County
or .....
Water will be used for: domestic Total depth of well: 79'
Size of drilled hole: 10" Weight of casing per linear foot: 9#
Thickness of casing: #10 Gage Temp. of water: 68
Diameter and length of casing: 80' x 6¼ I.D.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure .....
If nonflowing well give depth of standing water from surface: 30'
If flowing well describe control works .....
(Type and size of valve, etc.)
Date of commencement of well: April 21-55 Date of completion of well: Apr. 29-1955
Type of well rig: spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	20	20	silt
20	34	14	gravel in clay
34	38	4	gravel
38	54	16	gravel in clay
54	74	20	Broken lime
74	79	5	clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 54 to 74 ft.

Other aquifers .....

First water at 34-38 feet.

Casing perforated
from 54 to 79 ft.

Size of perforations
¼ x 10"
every other foot

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6 1/4 I.D 6 5/8 O.D	1' above	79'	80'	3/8" gravel pack 52'-79 Bal-cement

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

bales 15 G.P.M. to 50'
20 " 60'
25 " 70'

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Joseph E. Moty
Well Driller

By JEM

License No. 35

Dated May 2, 1955

(Not to be filled in by Driller)