

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57704
 Rec. 7 19
 Well No. _____
 Permit No. _____
Do not fill in

Owner George J. Wesley Driller Nevada Pump & Supply Company
 Address 2849 Fremont, Las Vegas, Nevada Address 412 S. 4th, Las Vegas, Nev. No. 133
 Location of well: 1/4 NE 1/4 Sec. 2, T. 22N/S, R. 61E, in Clark County
 or _____
 Water will be used for Domestic Total depth of well 120 feet
 Size of drilled hole 12" Weight of casing per linear foot 9 lb.
 Thickness of casing 12 ga. Temp. of water _____
 Diameter and length of casing 8" x 120 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 19 feet
 If flowing well describe control works _____
(Type and size of valve, etc.)
 Date of commencement of well Feb. 8, 1955 Date of completion of well Feb. 9, 1955
 Type of well rig Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Top Soil
2	11	9	Caliche
11	28	17	Hard Rock
28	33	5	Sand Water Bearing
33	41	8	Red Clay
41	57	16	Yellow Clay
57	63	6	Hard Rock
63	76	13	Sand Gravel Water Bearing
76	97	21	Red Clay
97	112	15	Sand & Gravel Water Bearing
112	117	5	Hard Rock
117	119	2	Coarse Gravel Water Bearing
119	120	1	Hard Yellow Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 28 to 33 ft.

Other aquifers 63 - 76
97 - 112
117 - 119

First water at 33 feet.

Casing perforated
 from 60 to 120 ft.

Size of perforations
1/16 x 6

