

ST.
 WELL LOG AND REPORT TO THE STATE
 ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 57726
 Rec. 19
 Well No. _____
 Permit No. _____
Do not fill in

Owner Ray Duncan Driller S.R. McKinney & Sons, Inc.

Address 23 New Mexico, Henderson, Nevada Address 1042 So. Main Lic. No 45

Location of well: NE 1/4 SW 1/4 Sec. 3, T22 N/S, R61 E, in Clark County

Water will be used for Domestic Total depth of well 120 ft

Size of drilled hole 12" to 50', 10" to 120' Weight of casing per linear foot 3/16"

Thickness of casing 3/16" Temp. of water _____

Diameter and length of casing 8" ID from 0 ft. to 120'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure. _____

If nonflowing well give depth of standing water from surface 17'

If flowing well describe control works _____
 (Type and size of valve, etc.)

Date of commencement of well 4/18/61 Date of completion of well 4/20/61

Type of well rig Eucyrus Erie 22 W

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Sand & gravel
3	20	17	caliche
20	35	15	clay & gravel
35	63	28	brown clay & gravel
63	65	2	gravel (water)
65	73	8	brown clay
73	80	7	gravel (water)
80	100	20	gravely clay
100	120	20	gravely clay (water)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 100 to 120 ft.

Other aquifers 63 to 65'

73 to 80'

First water at 63 feet.

Casing perforated

from 60 to 120' ft.

Size of perforations

3/16 x 10"

