

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57729  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Jimmy Fulcher Driller S. K. McKinney & Son  
 Address 300 Desert Inn Rd. Las Vegas Address 1042 S. Main Las Vegas Lic. No. 45  
 Location of well: SE 1/4 SW 1/4 Sec. 3, T. 22 N/S, R. 61 E, in Clark County  
 or SW. SE.  
 Water will be used for Domestic Total depth of well 158 ft.  
 Size of drilled hole 10" to 153 ft Weight of casing per linear foot 28 lb.  
 Thickness of casing 5/16" Temp. of water \_\_\_\_\_  
 Diameter and length of casing 8" I.D. to 158 ft.  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface XXXXX 19 ft.  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well Aug 28, 1953 Date of completion of well Aug 31, 1953  
 Type of well rig Sucyrus Erie 2A L. Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	18	18	caliche
18	25	7	clay and gravel
25	40	15	gravel water
40	55	15	clay and gravel
55	65	10	clay
65	115	50	clay and gravel water
115	140	25	clay and gravel water
140	150	10	cemented gravel
150	153	3	clay and gravel water
153	158	5	clay and gravel water

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 65 to 140 ft.  
 Other aquifers 150 to 158

---

First water at 25 feet.

8" Casing perforated  
 from 65 to 158 ft.

Size of perforations \_\_\_\_\_

