

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. **57745**  
 Rec. \_\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

I

Owner Wayne Smith Driller S.R. McKinney and Sons, Inc.

Address Paradise & Warm Springs Rd. LV Address 1042 So. Main Lic. No. 45

Location of well: SW 1/4 SE 1/4 Sec. 3, T. 22 N/S, R. 61 E, in Clark County County

Water will be used for Domestic Total depth of well 145 feet

Size of drilled hole 10" reamed 12" to 55 feet Weight of casing per linear foot 10 gauge

Thickness of casing 10 gauge Temp. of water \_\_\_\_\_

Diameter and length of casing 8" ID to 145 feet  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 27 feet

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well 4/1/60 Date of completion of well 4/6/60

Type of well rig Bucyrus Erie 22W

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	20	20	White Clay & Caliche
20	24	4	hard calich
24	39	15	White Clay
39	41	2	cemented gravel
41	44	3	Brown Clay
44	45	1	cemented gravel water
45	50	5	brown clay and gravel water
50	65	15	brown clay & gravel streaks water
65	75	10	light brown clay & gravel water
75	145	70	brown clay and gravel streaks water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 45 to 145 ft.

Other aquifers \_\_\_\_\_

First water at 45 feet.

Casing perforated  
 from 65 to 85  
105 to 145 ft.

Size of perforations  
3/16" x 10"



