

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57750  
 Rec. 19  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Joan Anderson Driller Patrick H. Thompson  
 Address 5932 Vermont St. Los Angeles California Address 217 So 26th St. LV. Nev. Lic. No. 192  
 Location of well: SW $\frac{1}{4}$  SW $\frac{1}{4}$  Sec. 4, T.22N/S, R.61E, in Clark County  
 or SW $\frac{1}{4}$ , SE $\frac{1}{4}$ , SW $\frac{1}{4}$ , SW $\frac{1}{4}$  of said section  
 Water will be used for Domestic Total depth of well 160'  
 Size of drilled hole 10" to 60' - 8" from 60' to 160' Weight of casing per linear foot 9.2#  
 Thickness of casing 10 guage Temp. of water cool  
 Diameter and length of casing 6" dia. 161' length  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 90'  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well Nov. 10, 1955 Date of completion of well Nov. 14, 1955  
 Type of well rig Cable tools

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	95	95	Cemented gravel
95	98	3	Sand
98	145	47	Cemented gravel
145	160	15	Sand & gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 145 to 160 ft.

Other aquifers 95 - 98

First water at 95 feet.

Casing perforated

from 130 to 160 ft.

Size of perforations

3/16 x 12 - 4 rows

