

WELL LOG AND REPORT TO THE STATE  
ENGINEER OF NEVADA

Log No. 57757  
 Rec. 7/19 1955  
 Well No. I  
 Perm. No. I  
 Do not fill in

Owner Blanche Connor Driller S.R. McKinney & Son

Address 3832 Dover Place, St. Louis, Mo. Address 1042 So. Main, L.V. Lic. No. 45

Location of well: NW 1/4 SE 1/4 Sec. 4, T22 N/S, R61 E, in Clark County

or NE 1/4 of SE 1/4 of NW 1/4 of SE 1/4 of Section 4, Twp. 22, Range 61

Water will be used for Domestic Total depth of well 150'

Size of drilled hole 12" to 50', 10" to 150' Weight of casing per linear foot 10 Gauge

Thickness of casing 10 Gauge Temp. of water

Diameter and length of casing ~~12" x 150'~~ 8" I.D. to 150'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 45'

If flowing well describe control works  
 (Type and size of valve, etc.)

Date of commencement of well 8 July 1955 Date of completion of well 11 July 1955

Type of well rig 72 Speed Star, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	4	4	Caliche	Chief aquifer (water-bearing formation) from <u>145</u> to <u>147</u> ft. Other aquifers <u>124 to 127</u> <u>105' to 108'</u> <u>94' to 97'</u> <u>68' to 71'</u> First water at <u>68</u> feet. Casing perforated from <u>70</u> to <u>150</u> ft. Size of perforations <u>3/16" x 10"</u>
4	21	17	Brown clay	
21	26	5	Caliche	
26	32	6	Gravel	
32	57	23	Brown clay	
57	68	11	Sand stone	
68	71	3	Red sand water	
71	82	11	Red clay	
82	94	12	Red clay	
94	97	3	Gravel water	
97	105	8	Red clay	
105	108	3	Red sand water	
108	115	7	Red clay	
115	118	3	Gravel	
118	124	6	Red clay	
124	127	3	Sand stone water	
127	145	18	Red clay	
145	147	2	Gravel water	
147	150	3	Red clay	

