

WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA

Log No. 57758
 Rec. 7/13 1952
 Well No.
 Permit No.
 Do not fill in

Owner Viola Conner Driller S.R. McKinney & Son
 Address 3822 Dover Place, St. Louis 8, Mo. Address 1042 South Main L.V. Lic. No. 45
 Location of well: NW 1/4 SE 1/4 Sec 4, T22 N/S, R61 E, in Clark County
 or SW 1/4 of SE 1/4 of NW 1/4 of SE 1/4 of Section 4, Twp. 22, Range 61 East
 Water will be used for Domestic Total depth of well 150'
 Size of drilled hole 12" to 50, 10" to 150' Weight of casing per linear foot 10 Gauge
 Thickness of casing 10 Gauge Temp. of water
 Diameter and length of casing 12 8" I.D. to 150'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure.....
 If nonflowing well give depth of standing water from surface. 45'
 If flowing well describe control works.....
 (Type and size of valve, etc.)
 Date of commencement of well July 2, 1955 Date of completion of well July 5, 1955
 Type of well rig 72 Speed Star, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	4	4	Caliche
4	24	20	Red Clay
24	28	4	Caliche
28	35	7	Brown clay
35	68	33	Brown clay
68	71	3	Caliche
71	74	3	Brown sand water
74	92	18	Brown clay
92	95	3	Sand stone water
95	107	12	Brown clay
107	110	3	Sand stone water
110	113	3	Brown sand water
113	124	11	Brown Clay
124	127	3	Sand stone water
127	130	3	Brown sand water
130	146	16	Brown clay
146	150	4	Gravel water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 146 to 150 ft.
 Other aquifers 127 to 130
124 to 127
107' to 113'
92' to 95'
71' to 74'

First water at 71 feet.

70 Casing perforated 150
 from to ft.

3/16" x 10" Size of perforations

