

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57924  
 Rec. \_\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_



*Do not fill in*

Owner Vernon R. Dent Driller Nevada Pump & Supply Co.  
 Address 1954 W. 148th St., Gardena, Calif. Address Las Vegas, Nevada Lic. No. 133  
 Location of well: NE 1/4 SW 1/4 Sec. 5, T. 22 N. S. R. 61 E. in Clark County  
 or \_\_\_\_\_  
 Water will be used for Domestic Total depth of well 150 feet  
 Size of drilled hole 12" Weight of casing per linear foot 12 lbs.  
 Thickness of casing 10 gauge Temp. of water \_\_\_\_\_  
 Diameter and length of casing 8" x 150'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 110 feet  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well June 8, 1955 Date of completion of well June 10, 1955  
 Type of well rig Cable Tools

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Top Soil
3	35	32	Boulders & Gravel
35	43	8	Caliche
43	95	52	Yellow Clay & Gravel
95	132	37	Red Clay-Gravel-Water
132	147	15	Sand and Water
147	150	3	Red Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 132 to 147 ft.

Other aquifers 95 - 132

First water at 96 feet.

Casing perforated from 100 to 150 ft.

Size of perforations 1/16" x 6"



