

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57933
 Rec. _____
 Well No. _____
 Permit No. _____

Do not fill in

Owner John A. Hall Driller S. R. McKinney & Son

Address 6567 Southside Dr. Los Angeles 22 Calif. Address 1042 S. Main Las Vegas No. 45

Location of well: N $\frac{3}{4}$ S $\frac{3}{4}$ Sec. 5, T. 22 N/S, R. 6E, in Clark County

or West $\frac{1}{2}$ of SE $\frac{1}{4}$ of NE $\frac{1}{4}$ of SW $\frac{1}{4}$ of Section 5, Twp. 22, Range 61 East

Water will be used for Domestic Total depth of well 175 ft.

Size of drilled hole 12" to 50 ft, 10" to 160 Weight of casing per linear foot 10 gauge

Thickness of casing 10 gauge 8" to 175 Temp. of water _____

Diameter and length of casing 8" I.D. to 175 ft.
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 120 ft.

If flowing well describe control works _____
 (Type and size of valve, etc.) _____

Date of commencement of well August 6, 1955 Date of completion of well Aug 11, 1955

Type of well rig 72 Speed Star, Spudler

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	sandy gravel
5	20	15	brown clay and gravel
20	33	13	cemented gravel
33	47	14	cemented gravel
47	85	38	brown gravelly clay
85	90	5	red sand and clay
90	95	5	brown clay
95	110	15	brown sandy clay
110	127	17	brown sand water
127	145	18	brown sand
145	150	5	brown sandy clay
150	160	10	brown gravelly clay
160	165	5	gravel water
165	170	5	brown sand and gravel water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 160 to 165 ft.

Other aquifers 165 to 170

110 to 127

First water at 110 ft. feet.

Casing perforated
 from 105 to 175 ft.

Size of perforations
3/16" x 10"

