

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57949
 Rec. 19
 Well No. _____
 Permit No. _____
 Do not fill in

Owner Joseph Peruzzi Driller S. R. McKinney & Son
 Address 715 North Tonopah, Las Vegas, Nevada Address 1012 S. Main Las Vegas Sec. No. 45
 Location of well: SE 1/4 SE 1/4 Sec. 5, T. 22 N/S, R. 61 E, in Clark County
 or SE 1/4 of SW 1/4 of NE 1/4 of SW 1/4 of Section 5, Twp. 22, Range 61 East
 Water will be used for Domestic Total depth of well 175 ft.
 Size of drilled hole 12" to 50 ft., 10" to 175 ft. Weight of casing per linear foot 10 guage
 Thickness of casing 10 guage Temp. of water _____
 Diameter and length of casing 8" I.D. to 175 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 95 ft.
 If flowing well describe control works _____
(Type and size of valve, etc.)
 Date of commencement of well March 9, 1955 Date of completion of well March 12, 1955
 Type of well rig Rucyrus Erie 24 L. Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	9	9	sandy clay
9	48	39	gravel
48	56	8	red clay
56	71	5	gravel
71	79	8	red clay
79	88	9	gravel
88	96	8	red clay
96	104	8	gravel
104	116	12	red clay
116	120	4	red sand water
120	140	20	red sandy clay
140	157	17	red sand and gravel water
157	167	10	red SHIX clay
167	175	8	gravel water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 167 to 175 ft.

Other aquifers 140 to 157
116 to 120

First water at 116 feet.

Casing perforated

from 135 to 175 ft.

Size of perforations

3/16" X 10"

