

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

57952

Log No. _____
 Rec. _____
 Well No. _____
 Permit No. _____
Do not fill in

Owner Alexander A. Rose Driller S. R. McKinney & Son
 Address 800 East Charleston, Las Vegas Address 1042 S. Main Las Vegas Lic. No. 45
 Location of well: SE 1/4 SW 1/4 Sec. 5, T. 22 N/S, R. 61 E, in Clark County
 or East 1/2 of SE 1/4 of SW 1/4 of Section 5, Twp 22, Range 61 East
 Water will be used for Domestic Total depth of well 160 ft.
 Size of drilled hole 12" to 50 ft, 10" to 180 Weight of casing per linear foot 24 lb.
 Thickness of casing 1/4" Temp. of water _____
 Diameter and length of casing 8" I.D. from 0 to 180 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 130 ft.
 If flowing well describe control works _____
(Type and size of valve, etc.)
 Date of commencement of well Oct 24, 1955 Date of completion of well Oct. 27, 1955
 Type of well rig Bucyrus Erie 24 L, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	soil and clay
6	55	49	HEAVILY cemented gravel
49	60	11	sandy clay
60	90	30	cement gravel
90	96	6	sandy clay
96	120	24	cement gravel
120	130	10	clay and gravel
130	145	15	clay and gravel water
145	160	15	cement gravel
160	175	15	clay and gravel water
175	180	5	gravel water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 160 to 180 ft.
 Other aquifers 130 to 145

First water at 140 feet.

Casing perforated
 from 140 to 180 ft.

Size of perforations
3/16" X 10"

