


WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57912
 Rec. _____
 Well No. _____
 Permit No. _____
 Do not fill in



Owner Tom Taney Standard Supply Driller Rodgers & Smith
 Address _____ Address 3200 Palomero Lic. No. 31
 Location of well: NE 1/4 SE 1/4 Sec 5, T. 22 N/S, R. 66 E, in Clark County
 or 0.3 miles S.W. of ... 200' West of HW 91
 Water will be used for Domestic Total depth of well 185
 Size of drilled hole 10 Weight of casing per linear foot 14
 Thickness of casing 10.5 ga Temp. of water _____
 Diameter and length of casing 8 OD/100
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 5 1/2 - 90 ft MP top of casing
 If flowing well describe control works _____
 (Type and size of valve, etc.) _____
 Date of commencement of well _____ Date of completion of well May 1952
 Type of well rig Spudger

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	12		sand gravel & clay	
12	35		white clay	
35	75		Brown clay	
75	105		Hard streaky clay & gravel	Chief aquifer (water-bearing formation) from <u>95</u> to <u>105</u> ft.
105	125		Some water at 96 ft	Other aquifers <u>155 to 165</u>
105	155		Red sandy clay	
155	165		Cement gravel water	First water at <u>96</u> feet.
165	185		Red clay	Casing perforated from <u>96</u> to <u>160</u> ft.
				Size of perforations <u>1/4</u> x <u>4</u>

