

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57972
 Rec. 10
 Well No. 10
 Permit No. 10

Owner Richard Woolfolk Driller Nevada Pump & Supply Company

Address 2505 St. George, N. Las Vegas, Nev. Address Las Vegas, Nevada

Location of well: NW 1/4 SW 1/4 Sec. 5, T. 22 N/S, R. 61 E, in Clark County

Water will be used for Domestic Total depth of well 157 feet

Size of drilled hole 10" Weight of casing per linear foot 9 lbs.

Thickness of casing 10 gauge Temp. of water _____

Diameter and length of casing 6" x 157'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 142 feet

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well June 25, 1955 Date of completion of well July 6, 1955

Type of well rig Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	Top Soil
5	70	65	Cemented Gravel
70	110	40	Limestone
110	130	20	Sandy Clay
130	141	11	Sandstone
141	153	12	Limestone
153	156	3	Gravel-Sand-Water
156	157	1	Limestone

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 153 to 156 ft.

Other aquifers _____

First water at 153 feet.

Casing perforated
 from 137 to 157 ft.

Size of perforations
1/16" x 6"



