

WELL LOG AND REPORT TO THE STATE  
ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 57974  
 Rec. \_\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*



Owner George Bernhard Driller S.R. McKinney & Sons, Inc.

Address 122 Exley, Las Vegas Address 1042 South Main Lic. No. 45

Location of well: Sec. 6, T22 N/S, R21 E, in \_\_\_\_\_ County

or 3. 132ft. of Gov. lot # 44, Sec. 6, Twp. 22 South, Range 61 East

Water will be used for Domestic Use Total depth of well 250 feet

Size of drilled hole 12" to 50', 10" to 250' Weight of casing per linear foot 10 gauge

Thickness of casing 10 gauge Temp. of water \_\_\_\_\_

Diameter and length of casing 8" ID from 0' to 250'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 160'

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well 9/19/62 Date of completion of well 9/27/62

Type of well rig Bucyrus Erie 22W

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	sandy clay & gravel
6	30	24	gravel & clay
30	45	15	gravel
45	100	55	gravel & clay
100	113	13	gravel streaks
113	116	3	gravel
116	130	14	sandy clay & gravel streaks
130	168	38	gravel & little clay
168	185	17	gravel (water)
185	250	65	cement gravel (water)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 185 to 250 ft.

Other aquifers 168 to 185

First water at 168 feet.

Casing perforated

from 150 to 250 ft.

Size of perforations

3/16" X 10"



