


WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 58004
 Rec. _____
 Well No. _____
 Permit No. _____
Do not fill in



Owner James L. Little Driller W. J. Mason
264 East 8th No. St. 1727 Santa Paula Drive
 Address Orem, Utah Address Las Vegas, Nevada Lic. No. 195

Location of well: NE 1/4 SE 1/4 Sec. 6, T. 22 N., R. 61 E. in Clark County
 or E 1/2 NE 1/4 SE 1/4 Section 6, Twp. 22 South Range 61 E.

Water will be used for domestic Total depth of well 230 feet

Size of drilled hole 12 inch Weight of casing per linear foot 22 pounds

Thickness of casing Quarter wall Temp. of water 76

Diameter and length of casing 160 feet 20 foot joints 8 1/8 I.D. 100 feet 6" I.D.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
liner 30 feet perforations & 30 feet overlap

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 158 feet

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well March 5th, 1955 Date of completion of well March 14th, 1955

Type of well rig Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	12	12	Sandy Clay
12	60	48	Sand & Gravel & Clay
60	85	25	Pea Gravel
85	160	75	River-bed gravel
160	190	30	Brown clay & gravel
190	230	40	Water bearing gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 190 to 230 ft.

Other aquifers None

First water at 190 feet.

Casing perforated
 from 180 to 210 ft.
 & from 220 to 230 ft.

Size of perforations
1/8 inch

