


WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA

Log No. 58008
 Rec.
 Well No.
 Permit No.
 Do not fill in



Owner Geo. A. Morgan Jr. Driller McKesson & Stock
 Address 118 No. 3rd St. Las Vegas Address 1629 N. Main. N. Las Vegas Lic. No. 200
 Nevada
 Location of well: $\frac{1}{4}$ Sec. $\frac{1}{4}$ Sec., T. N/S, R. E, in. Clark County
 or. Sec. 6 T22S. R. 61 E. W. $\frac{1}{2}$ NE $\frac{1}{4}$ SW $\frac{1}{4}$ SE $\frac{1}{4}$ Mount. Diablo Meridian
 Water will be used for Domestic Total depth of well 180
 Size of drilled hole 8 inch Weight of casing per linear foot 11.8
 Thickness of casing 10 Gauge Temp. of water Cool
 Diameter and length of casing 8 inch 180 feet
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure
 If nonflowing well give depth of standing water from surface 153
 If flowing well describe control works
 (Type and size of valve, etc.)
 Date of commencement of well June 12 1955 Date of completion of well June 14 1955
 Type of well rig Keystone # 50

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5		Silt & Sand
5	12		Loose Gravel
12	138		Cemented Gravel
138	167		Brown Shale
167	175		Gravel (Water)
175	180		Cemented Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 167 to 175 ft.
 Other aquifers.....
 First water at 167 feet.
 Casing perforated
 from 140 to 180 ft.
 Size of perforations
 $\frac{1}{4}$ in. 6 inches long
 staggered around casing

