

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 58020
 Rec. 19
 Well No. _____
 Permit No. _____
Do not fill in

Owner Dr. Erich Winters Driller S.R. McKinney & Son
 Address 1071 Hasset Street, Las Vegas, Nev. Address 1042 So. Main, Las Vegas, Nev. Lic. No. 45
 Location of well: NE 1/4 SE 1/4 Sec. 6, T. 22 N/S, R. 61 E, in Clark County
 or E 1/2 of NE 1/4 of NE 1/4 of SE 1/4, of Section 6, Twp. 22, Range 61
 Water will be used for Domestic Total depth of well 200'
 Size of drilled hole 12" to 50', 10" to 200' Weight of casing per linear foot 10 Guage 28 lb.
 Thickness of casing 10 Guage 1/4" wall Temp. of water _____
 Diameter and length of casing 8 to 159' 10 Guage, 159' to 200' 1/4" wall
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 135'
 If flowing well describe control works _____
 (Type and size of valve, etc.) _____
 Date of commencement of well May 31, 1955 Date of completion of well June 3, 1955
 Type of well rig Bucyrus Erie 24L, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	30	30	Cement gravel
30	55	25	Cement gravel
55	60	5	Clay & Gravel
60	70	10	Sand Stone
70	100	30	Cement Gravel
100	145	45	Sandy Clay
145	155	10	Cement Gravel
155	165	10	Sand, Water
165	170	5	Clay & Gravel
170	175	5	Cement gravel
175	180	5	Cement gravel water
180	190	10	Cement gravel
190	200	10	Cement gravel water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 190 to 200 ft.

Other aquifers 175' to 180'
155' to 165'

First water at 155 feet.

Casing perforated
from 155 to 200 ft.

Size of perforations
3/16" X 10"

