

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 58452  
 Rec. No. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Ralph John Poler Driller Effinger Drill & Pump Serv.  
 Address 5900 E. Charleston Address Box 589 Lic. No. 212  
 Location of well: S.W. 1/4 S.W. 1/4 Sec. 34, T. 20 N/S, R. 6162 E, in Clark County  
 or Hedge Lane Lot 4 Blk #2 Tract #2 Greenacres  
 Water will be used for Domestic Total depth of well 100 feet  
 Size of drilled hole 12 Inch Weight of casing per linear foot 8.64 lbs.  
 Thickness of casing 10 Gauge Temp. of water \_\_\_\_\_  
 Diameter and length of casing 6"OD 100 feet  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 34' 8" from top of casing  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well May 13, 1958 Date of completion of well May 14, 1958  
 Type of well rig "71 Speed Star"

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	26	26	Yellow Clay
26	31	5	Gravel (Water)
31	39	8	Limestone (Water)
39	54	15	White Clay
54	56	2	Limestone (Water)
56	60	4	White Clay
60	69	9	Yellow Clay
69	73	4	Sandstone (Water)
73	85	12	Yellow Clay
85	88	3	Sandstone (Water)
88	100	12	Red Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation) 85 88

from \_\_\_\_\_ to \_\_\_\_\_ ft.

Other aquifers 69-73  
54-56

26

First water at \_\_\_\_\_ feet.

Casing perforated 80 100

from \_\_\_\_\_ to \_\_\_\_\_ ft.

1/8" x 15'



