GENERAL IMPROVEMENT & INVESTMENT CO.

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 58522
Rec. 19
Well No. .....
Permit No. 15844
Do not fill in

Kork T.V. Station

Owner Ted Anderson — Driller Allen Water Well Service Co.

Address 309 So. 3rd. St. — Address 911 So. Main St. — Lic. No. 40

Location of well: SE ¼ ¼ Sec. 7, T. 21 N/S, R 62 E, in Clark County

or

Water will be used for Domestic — Total depth of well 100

Size of drilled hole 8" — Weight of casing per linear foot 22 lbs.

Thickness of casing ½ wall — Temp. of water

Diameter and length of casing 8 5/8 O.D.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 16'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well Sept. 14, 1954 — Date of completion of well Sept. 17, 1954

Type of well rig Keystone 50A Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	1	1	Top Soil
1	22	21	Caliche & Clay
22	35	13	Sandy clay and gravel
35	63	28	Sticky clay
63	75	12	Sandy clay and gravel
75	87	12	Cemented Gravel
87	100	13	Soft Clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 22 to 35 ft.

Other aquifers 63-75

First water at 22 feet.

Casing perforated

from 40 to 100 ft.

Size of perforations

½ x 4 4 around on 12" centers.

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8 5/8 O.D.	0	102	102	¼wall. Two foot of casing above ground level

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed [illegible] Well Driller

By Allen Water Well Serv

License No. 40

Dated Sept 20, 1954

(Not to be filled in by Driller)