WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 58528
Rec. 19
Well No.
Permit No.
Do not fill in

Owner W. W. McCown Driller O. A. Effinger

Address Boulder City Highway (4 Mile) Address Las Vegas Nev. Lic. No. 105

Location of well: NE ¼ NW ¼ Sec. 7, T 21 N/S, R 62 E, in Clark County

or

Water will be used for Domestic Total depth of well 125 FT

Size of drilled hole 8 in. Weight of casing per linear foot 9 LB.

Thickness of casing 10 G Temp. of water

Diameter and length of casing 6 in. O.D. — 40 FT
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 19 FT - 9 IN.

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well Aug. 29, 1952 Date of completion of well Aug. 30, 1952

Type of well rig "71 Star"

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Yellow Clay
3	15	12	Red Sandy Clay
15	27	12	Yellow Clay
27	29	2	Red Sand Rock (Water)
29	53	24	Red Sticky Clay
53	54	1	Red Sand Rock
54	78	24	Yellow Clay
78	84	6	White Clay
84	110	26	Yellow Clay
110	113	3	Sand Rock
113	116	3	Sandy Clay
116	121	5	Gravel (Water)
121	125	4	Red Sticky Clay
~~125~~			

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 27 to 29 ft.

Other aquifers 116 - 121

First water at 29 feet.

Casing perforated

from to ft.

Size of perforations

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6 IN. O.D.	0	40	40	CEMENTED 0 TO 38 FT.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Eppinger Bros
Well Driller

By C. H. Eppinger

License No. 105

Dated Oct 3, 1952

(Not to be filled in by Driller)