

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 58550  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner John C. Duncan Driller Effinger Drill & Pump Serv.  
 Address 15 West Owens Address 5438 W. Duncan Drive Lic. No. 212  
 Location of well: SE 1/4 SE 1/4 Sec. 8, T 21N/S, R. 62, in Clark County  
 or Linden Street  
 Water will be used for Domestic Total depth of well 120 feet  
 Size of drilled hole 12 Inch Weight of casing per linear foot \_\_\_\_\_  
 Thickness of casing 8 Gauge Temp. of water \_\_\_\_\_  
 Diameter and length of casing 8 1/2 ID 120 Feet  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 16' 8" from top of casing  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well May 4, 1960 Date of completion of well May 6, 1960  
 Type of well rig "71 Speed Star"

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	Sand
5	20	15	Red Clay
20	26	6	Brown Clay
26	59	33	Gravel (Water)
59	80	21	Hard Clay
80	100	20	Sandy Clay
100	115	15	Sand & Gravel (Water)
115	120	5	Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 100 to 115 ft.

Other aquifers 26-59

First water at 26 feet.

Casing perforated  
from 70 to 120 ft.

Size of perforations  
1/8 x 12"

