

WELL LOG AND REPORT TO THE STATE  
ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 58559  
 Rec. 19  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner A. E. Fleming Driller S. H. McKinney & Sons, Inc.

Address Aloha & Happy Valley Rds., L.V. Address 1042 South Main Lic. No. 45

Location of well: SE 1/4 SE 1/4 Sec. 8, T. 21N/S, R. 62E, in Clark County

Water will be used for Domestic Total depth of well 100'

Size of drilled hole 12" to 50', 10" to 100' Weight of casing per linear foot 10 gauge

Thickness of casing 10 gauge Temp. of water \_\_\_\_\_

Diameter and length of casing 8" ID from 0' to 100'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 26'

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well 12/4/62 Date of completion of well 12/6/62

Type of well rig Bucyrus Erie 24L

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	sand
3	5	2	gravel
5	10	5	sand
10	15	5	sandy clay
15	37	22	gravely clay
37	45	8	gravel (water)
45	58	13	clay
58	100	42	gravely clay (water)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 37 to 45 ft.

Other aquifers 58 to 100'

First water at 37' feet.

Casing perforated

from 40 to 100' ft.

Size of perforations

3/16" X 10"

