WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 58573
Rec. 19
Well No.
Permit No.
Do not fill in

Owner: O M Gullard Driller: O M Gullard

Address: 27C Victory Village Address: Box 432 Henderson Lic. No. 115

Location of well: N½ ¼ SE ¼ Sec. 8, T. 21 N/S, R 62 E, in Clark County

or MDBM

Water will be used for: Domestic Use Total depth of well: 100 ft.

Size of drilled hole: 6" Weight of casing per linear foot: 10 lbs.

Thickness of casing: 1/8" Temp. of water:

Diameter and length of casing: 6" 60 ft
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 18 ft.

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: 9/5/52 Date of completion of well: 9/10/52

Type of well rig: Fort Worth Spudder - Model L

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	20	20	Red Clay
20	22	2	Gravel - First Water
22	35	13	Red Clay
35	40	5	Red Clay & Rock
40	41	1	Sand
41	60	19	Yellow Clay
60	63	3	Gravel
63	94	31	Yellowish Clay
94	95	1	Rock
95	98	3	Sand & Gravel - 2nd Water
98	100	2	Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 95 to 98 ft.

Other aquifers

First water at 22 feet.

Casing perforated

from 45 to 60 ft.

Size of perforations

½" Wide 2" long

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0	60'	60'	Cemented-in 40 feet

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed O M Gilbert
Well Driller

By.....

License No. 115

Dated Oct 10, 1952

(Not to be filled in by Driller)