

**WELL LOG AND REPORT TO THE STATE ENGINEER
OF NEVADA**

Log No. 58576
 Rec. 19
 Well No. 18618
 Permit No. 18618
 Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Don Carr Driller Patrick H. Thompson

Address Las Vegas, Nevada Address Las Vegas, Nevada Lic. No. 192

✓ Location of well NE 1/4 Sec 74, T19N/S, R60E, in Clark County

or SE 1/4 SE 1/4 SEC 9 T22S R61 177-09-804-008

Water will be used for Domestic QM Total depth of well 300'

Size of drilled hole 10" Weight of casing per linear foot 13#

Thickness of casing 10 ga. Temp. of water cool

Diameter and length of casing 8 5/8 dia. 300' length
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface 70'

If flowing well describe control works.....
(Type and size of valve, etc.)

Date of commencement of well June 7, 1967 Date of completion of well June 17, 1967

Type of well rig cable tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Sandy clay
3	5	2	Caliche
5	25	20	Brown clay
25	30	10	Gravel & clay
30	35	5	Gravel & clay
35	50	15	Gravel with clay stks
50	70	20	Brown clay
70	150	80	Gravel & brown clay stks
150	160	10	Brown clay w/gravel stks
160	168	8	Gravel
168	172	4	Brown clay
172	300	128	Cement gravel

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)
 from 172 to 300 ft.

Other aquifers 70-150
160-168

First water at 70 feet.

Casing perforated
 from 100 to 300 ft.

Size of perforations
3/16 x 12 4 Rows