WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 58577
Rec. ..... 194....
Well No. .....
Permit No. .....
Do not fill in

Owner Leo Holden Well Driller Pulon Mitchell

Address 2104 Mesquite L.V. Address 910 E. College Lic. No. 63

Location of well: SW ¼ SE ¼ Sec 8, T. 21 N/S, R 62 E, in Clark County

or Vegas Valley Estates, Linden near Aloa Rd.

Water will be used for domestic Total depth of well 80'

Size of drilled hole 8" Weight of casing per linear foot .....

Thickness of casing 14 gauge Temp. of water .....

Diameter and length of casing 40' of 8" Casing
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure Non flowing

If nonflowing well give depth of standing water from surface 25 ft.

If flowing well describe control works .....
(Type and size of valve, etc.)

Date of commencement of well April 9, 1954 Date of completion of well April 13, 1954

Type of well rig 71 speed star

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	clay
2	10	8	dry gravel
10	25	15	Brown Clay
25	30	5	water-gravel
30	50	20	Brown Clay
50	55	5	Water gravel
55	65	10	sticky clay
65	70	5	water gravel
70	80	10	sticky clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 50 to 55 ft.

Other aquifers 65-70-
Gravel

First water at 25 feet.

Casing perforated

from None to ..... ft.

Size of perforations

None

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8"	0	40	40	40' of 8" Casing and 1 yd of Sand + Cement.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Rex Hargore
Well Driller

By .....

License No. 63

Dated May 24, 1954

(Not to be filled in by Driller)