

WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 58579
 Rec. No. 19
 Well No. 1
 Permit No. 1
 Do not fill in

Owner Ed Hoppe Driller S. H. McKinney & Sons, Inc.

Address 417 Carson Ave. Address 1042 So. Main Lic. No. 45

Location of well: SE 1/4 SE 1/4 Sec. 8, T. 21N/S, R. 62E, in Clark County

Water will be used for Domestic Use Total depth of well 100 feet

Size of drilled hole 12" to 50 feet, 10" to 100" Weight of casing per linear foot 3/16" wall

Thickness of casing 3/16" wall Temp. of water

Diameter and length of casing 8 5/8" from 0 feet to 100 feet
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 25 feet

If flowing well describe control works
 (Type and size of valve, etc.)

Date of commencement of well 4/13/61 Date of completion of well 4/15/61

Type of well rig Russris Erie 24 L

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	7	7	top soil
7	20	13	gravel & clay
20	37	17	sandy clay
37	40	3	gravel (water)
40	43	3	sandy clay
43	47	4	gravel & clay (water)
47	60	13	red clay & gravel
60	62	2	gravel
62	80	18	gravelly clay (water)
80	90	10	clay
90	100	10	gravelly clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 62 to 80 ft.

Other aquifers 43 to 47 ft.
37 to 40 ft.

First water at 37 feet.

Casing perforated
 from 60 to 100 ft.

Size of perforations
3/16" x 10"

