

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 58635
 Rec. _____ 19____
 Well No. _____
 Permit No. _____
Do not fill in

Owner Victor Selby Driller S.R. McKinney & Sons, Inc.

Address 615 Mojave Road, Las Vegas Address 1012 So. Main Lic. No. 45

Location of well: Se 1/4 Se 1/4 Sec. 8, T. 21N/S, R. 62 E, in Clark County
 or _____

Water will be used for Domestic Total depth of well 120 feet

Size of drilled hole 12" to 50', 10" to 120' Weight of casing per linear foot 10 gauge

Thickness of casing 10 gauge Temp. of water _____

Diameter and length of casing 5/8" OD from 0 to 120'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 40'

If flowing well describe control works _____
 (Type and size of valve, etc.)

Date of commencement of well 10/24/61 Date of completion of well 10/26/61

Type of well rig Bucyrus Erie 22W

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	top soil
5	15	10	sandy clay
15	25	10	gravely clay
25	38	13	brown clay
38	48	10	gravel (water)
48			
48	75	27	brown clay with gravel streaks
75	85	10	gravely clay
85	100	15	brown sandy clay
100	120	20	gravley clay (water)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 38 to 48 ft.

Other aquifers 100 to 120

First water at 38 feet.

Casing perforated

from 60 to 120 ft.

Size of perforations

3/16" x 10"

