Log No. 58813
Rec. 19
Well No. 1
Permit No. .....
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner W.B.Bierce Driller Nov Charlie Cribbs

Address Bolder City. Address 27I0 Palomino lane Lic. No. 70

Location of well: NW¼SE¼ Sec. 18, T. 21 N/S, R. 62 E, in Clark County

or Sandhill road and Tumbleweed lane Known as the broad acres est.

Water will be used for Domestic Total depth of well I60

Size of drilled hole I0 Weight of casing per linear foot

Thickness of casing 3/I6 Temp. of water

Diameter and length of casing 8 5/8
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface I5

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well spudde4r II 24 Date of completion of well II 26

Type of well rig spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
00	4	4	sand and gravel
4	I0	6	colechie
I0	20	I0	red clay
20	25	5	sand rock and gravel water
25	60	35	red clay
60	I60	I00	red clay ribbed with soft s
			sand rock I to 3 ft thick water bearing

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 60 to I00 ft.

Other aquifers

First water at 20 feet.

Casing perforated
from 60 to I60 ft.

¼ in
Size of perforations

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
	00	160	160	85/8 casing perforated and graveled to 50 ft of surface cemented from 50 ft to surface with 2 yds. ready mix

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Charlie Cobb
Well Driller

By L B Rodgers

License No. 76 156

Dated Nov 26, 1960

(Not to be filled in by Driller)