

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

LVD

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 58878  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
 Do not fill in

Owner G. E. an/or Glenn Kuhry Driller Douglas Stagle

Address 3890 East Tumbleweed--- L. V. Address 4518 E. Vegas Valley Dr Lic. No. 137

Location of well: SW NE 1/4-33 1/4 Sec. 18, T. 21N/S, R. 62E, in Clark County  
 or at above Address on Tumbleweed just East of Sandhill

Water will be used for Domestic Total depth of well 150 Ft.

Size of drilled hole 12" for 8" casing Weight of casing per linear foot 12.15 per Ft.

Thickness of casing 10 Gage Temp. of water Cool

Diameter and length of casing 8 5/8" O.D. x 150 Ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 19 Ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well November 12 1966 Date of completion of well November 19 1966

Type of well rig Buckrus-Erie 22W Series # 2

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	27 1/2	27 1/2	Lt. Brn. Clay.
*27 1/2	31	3 1/2	Gravel & Water
31	57	26	Red Clay
57	58	1	Hard Rock
*58	60	2	Sand & Water
60	79	19	Sandy Brn. Clay
79	80	1	Rock
*80	86	6	Pea Gravel & Water
86	110	24	Red Clay
*110	140	30	Series of Clay, sand, & Water
140	150	10	Dark Red Clay

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 110 to 140 ft.

Other aquifers 27 1/2 to 31  
58 to 60  
80 to 86

---

First water at 27 1/2 feet.

Casing perforated  
 from 50 to 150 ft.

Size of perforations  
1/8" x 12"

