WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 58898
Rec. 19
Well No. .....
Permit No. .....
Do not fill in

Owner: Mary Anne Walker Driller: Effinger Bros.

Address: 1720 Lewis Street Address: 1001 Artesia Way Lic. No. 105

Location of well: ..... ¼ ..... ¼ Sec. ....., T. ..... N/S, R. ..... E, in Clark County

or N½SE¼SE¼SW¼ Section 18 T21S R62E

Water will be used for: Domestic Total depth of well: 200 feet

Size of drilled hole: 12 Inch Weight of casing per linear foot: 12.06 lbs.

Thickness of casing: 10 Gauge Temp. of water: .....

Diameter and length of casing: 8 5/8"OD 200 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: .....

If nonflowing well give depth of standing water from surface: 5' from top of casing

If flowing well describe control works: .....
(Type and size of valve, etc.)

Date of commencement of well: May 28, 1955 Date of completion of well: June 4, 1955

Type of well rig: "71 Speed Star"

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Sand
3	22	19	Caliche
22	33	11	Yellow Clay
33	35	2	Sand (Water)
35	47	12	Yellow Clay
47	49	2	Limestone (Water)
49	65	16	Red Sandy Clay
65	69	4	Limestone (Water)
69	72	3	Clay
72	75	3	Sandstone
75	82	7	Red Clay
82	87	5	Limestone
87	101	14	Red Clay
101	102	1	Gravel (Water)
102	115	13	Limestone
115	117	2	Red Sticky Clay
117	123	6	Limestone
123	132	9	Red Sandy Clay
132	135	3	Gravel (Water)
135	156	21	Red Sandy Clay
156	162	6	Gravel (Water)
162	188	26	Red Clay
188	191	3	Gravel (Water)
191	200	9	Sticky Clay & Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 188 to 191 ft.

Other aquifers: 156-162
132-135
101-102
65-69
47-49

First water at 33 feet.

Casing perforated
from 60 to 200 ft.

Size of perforations
1/8" X 12"

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
5/8 OD	0	200	200	Cemented from 0 to 50 feet Perforated from 50 to 200 feet 5 yards of pea gravel 2 yards of cement

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Effinger Bros.
Well Driller

By O. F. Effinger

License No. 105

Dated June 4, 19 55

(Not to be filled in by Driller)