


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



58911

Log No. \_\_\_\_\_  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Raymond H. Bowman Driller Boiling Bros.  
 Address 327 1/2 South Donath Street Address 1001 Antonia Way Lic. No. 212  
 Location of well: \_\_\_\_\_ 1/4 \_\_\_\_\_ 1/4 Sec. \_\_\_\_\_, T. \_\_\_\_\_ N/S, R. \_\_\_\_\_ E, in \_\_\_\_\_ Glas County  
 or Blanchard Section 19 T12S R6E  
 Water will be used for Domestic Total depth of well 120 feet  
 Size of drilled hole \_\_\_\_\_ Weight of casing per linear foot 6.9 lbs.  
 Thickness of casing 10 Guage Temp. of water \_\_\_\_\_  
 Diameter and length of casing 6" 60 feet  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface \_\_\_\_\_  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well November 8, 1955 Date of completion of well November 4, 1955  
 Type of well rig "71 Speed Star"

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
			Well was originally drilled by Hoisinger Drilling Co.	
			60' 6" Guage liner was dropped in well. This well now meets requirements of the third option wells.	Chief aquifer (water-bearing formation) from _____ to _____ ft.
			61' from top of 8" casing to top of 6" liner.	Other aquifers _____
			Liner is perforated.	First water at _____ feet.
				Casing perforated from _____ to _____ ft.
				Size of perforations _____



