

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 58912
 Rec. 19
 Well No. _____
 Permit No. _____
Do not fill in

Owner G. L. Boyle Driller S. R. McKinney & Son
 Address 18 Lufberry, Wherry Housing, Las Vegas Address 1042 S. Main Las Vegas Lic. No. 45
 Location of well: SW 1/4 SW 1/4 Sec. 19, T21 N/S, R62 E, in Clark County _____
 or West 1/2 of NE 1/2 of SW 1/4 of SW 1/4 of Section 19, Twp. 21, Range 62 East.
 Water will be used for Domestic Total depth of well 160 ft.
 Size of drilled hole 160 ft. Weight of casing per linear foot 28 lb.
 Thickness of casing 1/4" Temp. of water _____
 Diameter and length of casing 8" I.D. to 160 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 10 ft.
 If flowing well describe control works _____
(Type and size of valve, etc.)
 Date of commencement of well Oct 11, 1955 Date of completion of well Oct 12, 1955
 Type of well rig Bucyrus Erie 24 L. Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material.
0	5	5	soil and clay
5	14	9	caliche
14	60	46	sandy clay water
60	125	65	sandy clay water
125	145	20	sandy clay and gravel
145	153	8	sandy clay and
153	160	7	gravel water

NEVADA STATE ENGINEER

APPROVED 10/14/55

By L. M. V. [Signature]

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 153 to 160 ft.

Other aquifers 14 to 125

First water at 14 ft. feet.

Casing perforated
 from 120 to 160 ft.

Size of perforations
3/16" X 10"

