X WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 58918
Permit No.
Basin 084

NOTICE OF INTENT NO. 33217

1. OWNER Harold Ward
MAILING ADDRESS P.O. Box 51745
Sparks Nevada 89434

ADDRESS AT WELL LOCATION Wrangler Road
Polomino Valley

2. LOCATION NE ¼ SW ¼ Sec 20 T 22 O/S R 22 EAST WASHOE County

PERMIT NO. (Issued by Water Resources) 077-400-15 (Parcel No.) Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Brown D.G.		0	15	
red andisite		15	65	
Gray clay		65	80	
Red andesite		80	210	
Multi colored volcanic rock		210	310	
Clear Quartz		310	345	
Multi colored besalt		345	395	
Multi colored volcanic rock		395	445	
Gray silica sand		445	500	
Multi colored quartz		500	545	
Orange & clear granite		545	560	
Multi colored granite		560	635	
Red & green volcanic gravels		635	650	
Gravels & red clay orange & clear		650	670	
Orange & clear granite		670	750	
T.D. 750'				

Date started June 25, 19 96
Date completed July 1, 19 96

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

Well bore dry-abandon well
Shovel cutting back in hole to 50'
Pour 7400 lbs of cement grout to
seal to surface.

8. WELL CONSTRUCTION
Depth Drilled 750 Feet Depth Cased 0 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
10-5/8 Inches	0 Feet	50 Feet
8-1/2 Inches	50 Feet	750 Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)

Perforations:
Type perforation
Size perforation
From feet to feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☐ No
Depth of Seal
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout
Gravel Packed: ☐ Yes ☐ No
From feet to feet

9. WATER LEVEL
Static water level feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name A.S.A.P. Pump & Well Service Inc. (Contractor)
Address 1800½ Frazer Avenue (Contractor)
Sparks Nevada 89431
Nevada contractor's license number issued by the State Contractor's Board 35387-A
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1509-T1
Signed Larry Welch (By driller performing actual drilling on site or contractor)
Date Aug 1, 1996

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627