

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 59068
 Rec. _____ 19____
 Well No. _____
 Permit No. _____
 Do not fill in

Owner Harrison & Foster # 2 (House well); Driller S. R. McKinney & Son

Address Box 1045, Las Vegas, Nevada Address 1042 S. Main, Las Vegas Lic. No. 45

Location of well: NW 1/4 NW 1/4 Sec. 19, T. 21 N, R. 62 E, in Clark County

or _____

Water will be used for Domestic Total depth of well 260

Size of drilled hole 10" to 63 ft., 8" to 260 Weight of casing per linear foot 26 lb.

Thickness of casing 1/2" Temp. of water _____

Diameter and length of casing 8" I.D. to 66 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface Surface

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well April 25, 1952 Date of completion of well May 1, 1952

Type of well rig Bucyrus Erie 24 L, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	1	1	Sand
1	4	3	Soft caliche
4	35	31	Brown sandy clay
35	40	5	Caliche, water
40	60	20	Brown sandy clay
60	63	3	Caliche, hard, water
63	80	17	Red sandy clay
80	82	2	Red sandstone, water
82	130	48	Red sandy clay
130	132	2	Gravel, water
132	190	58	Red sandy clay
190	200	10	Red sandy clay with thin sandstone shelves.
200	230	30	Red clay
230	260	30	Red clay with sandstone shelves about 2 ft. thick every five ft. Water in sandstone shelves.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 230 to 260 ft.

Other aquifers 80 to 82
130 to 132

First water at 35 feet.

Casing perforated
 None from _____ to _____ ft.

Size of perforations _____

