


WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 59117
 Rec. _____ 19____
 Well No. _____
 Permit No. _____
Do not fill in



Owner R.F. Slaughter Driller Patrick H. Thompson

Address Las Vegas, Nevada Address 217 S. 26th St. Lic. No. 192

Location of well: NW 1/4 - SW 1/4 Sec. 19, T21 N/S, R6 E, in Clark County

Water will be used for Domestic to 200 Total depth of well 200

Size of drilled hole 12" to 50' 10" from 50' Weight of casing per linear foot 12 lb.

Thickness of casing 10 guage Temp. of water cool

Diameter and length of casing 8 5/8 inch diameter -- 201 ft. length
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 80 feet

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well April 8, 1960 Date of completion of well April 11, 1960

Type of well rig Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	7	7	Surface Sand	
7	9	2	Caliche	
9	15	6	White Clay	
15	17	2	Caliche	Chief aquifer (water-bearing formation) from <u>185</u> to <u>190</u> ft.
17	50	33	White Clay	Other aquifers <u>80 to 81</u>
50	60	10	Red Clay	<u>90 to 96</u>
60	65	5	Gravel	<u>130 to 135</u>
65	80	15	Red Clay	<u>175 to 180</u>
80	81	1	Red Clay and Water	
81	99	9	Red Clay	
90	96	6	Brown Clay & Gravel	
			Water	
96	130	34	Brown Clay	First water at <u>80</u> feet.
130	135	5	Gravel	
135	160	25	Brown Clay	
160	165	5	Water	
165	175	10	Brown /Clay	Casing perforated
175	180	5	Red Clay & Gravel & Water	from <u>100</u> to <u>200</u> ft.
180	185	5	Red Clay & Gravel	
185	190	5	Gravel	
190	200	10	Brown Sandy Clay, Gravel	Size of perforations <u>3/16 by 12 4 rows</u>
			Water	

