

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

59176  
 Log No. 59176  
 Rec. ....  
 Well No. ....  
 Permit No. ....  
*Do not fill in*

Owner Roy Brown Driller MCGARVIE PLUMBING AND WELDING  
c/o Charleston Hotel  
 Address Las Vegas, Nevada Address 313 Tonapah Hwy. Lic. No 132  
 Location of well: SW $\frac{1}{4}$ , SW $\frac{1}{4}$ , SE $\frac{1}{4}$ , SW $\frac{1}{4}$ , SEC. 16, T22S, R61E, MDM. Clark County, Nevada  
1/4 Sec. T N/S, R E, in Clark County

Water will be used for Domestic Total depth of well 200'

Size of drilled hole 8" Weight of casing per linear foot .....

Thickness of casing 8"x 10 guage Temp. of water .....

Diameter and length of casing 8"x  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface 75'

If flowing well describe control works .....

Date of commencement of well May 19, 1955 Date of completion of well May 22, 1955

Type of well rig Cable

LOG OF FORMATIONS				Water-bearing Formation, Casing Perforations, Etc.
From feet	To feet	Thickness feet	Type of material	
0	80	80	Brown Sticky clay	Chief aquifer (water-bearing formation)
80	160	80	Sticky red and brown clay	from <u>125</u> to <u>200</u> ft.
160	200	40	Gray sandy shale	Other aquifers.....
				First water at <u>125</u> feet.
				Casing perforated
				from <u>140</u> to <u>200</u> ft.
				Size of perforations
				<u>1/8x6 5Rows 24" centers</u>

