

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 59210  
 Rec. Aug 19 1955  
 Well No. \_\_\_\_\_  
 Permit No. 1527  
*Do not fill in*

Owner Gladys Gerber Driller S. R. McKinney & Son

Address R.R. 1, Box 138, Las Vegas, Nev. Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: SE 1/4 SW 1/4 Sec 16, T22 N/S, R61 E, in Clark County  
 or NE 1/4 of SW 1/4 of SE 1/4 of SW 1/4 of Section 16, Twp. 22, Range 61 East.

Water will be used for Domestic Total depth of well 120 ft.

Size of drilled hole 10" to 50 ft, 12" 8" to 120" Weight of casing per linear foot 24 lb.

Thickness of casing 1/4" Temp. of water \_\_\_\_\_

Diameter and length of casing 6" I.D. to 120 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 77 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Aug. 17, 1955 Date of completion of well Aug 18, 1955

Type of well rig Bucyrus Erie 24 L. Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	sandy clay
3	6	3	caliche
6	35	29	cement gravel
35	39	4	sandy clay
39	60	21	cement gravel
60	69	9	clay and gravel
69	75	6	cement gravel
75	85	10	sandy clay
85	110	25	clay and gravel
110	120	10	gravel water

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 110 to 120 ft.

Other aquifers \_\_\_\_\_

---

First water at 110 ft. feet.

Casing perforated  
 from 100 to 120 ft.

Size of perforations  
3/16" X 10"

