

SX-

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 59428
 Rec. 19
 Well No. _____
 Permit No. _____
Do not fill in

Owner Marvin Rambo Driller S.R. McKinney & Sons, Inc.

Address 635 Tyson Road Address 1042 South Main Lic. No. 45

Location of well: SW¹/₄ SE¹/₄ Sec. 16, T22 N/S, R61 E, in Clark County

Water will be used for Domestic Use Total depth of well 250'

Size of drilled hole 12" to 50', 10" to 250' Weight of casing per linear foot 10 Gauge

Thickness of casing 10 Gauge Temp. of water _____

Diameter and length of casing 8" ID from 0' to 250'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 94'

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well 4-23-65 Date of completion of well 4-30-65

Type of well rig Bucyrus Erie 32W

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Sand
2	8	6	caliche
8	55	47	cement gravel
55	113	48	brown gravelly clay
113	118	5	gravel (water)
118	130	12	brown gravelly clay
130	134	4	gravel
134	250	116	cement gravel (water)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 134 to 250' ft.

Other aquifers 113 to 118'

First water at 113 feet.

Casing perforated from 120' to 250' ft.

Size of perforations

3/16" X 10"



