

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log of well after deepened.

Log No. **59432**  
 Rec. **19**  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

*Do not fill in*

Owner Burd O. Rohde Driller S. R. McKinney & Son

Address P.O. Box 7, Arden, Nevada Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: NW 1/4 NW 1/4 Sec 16, T22 N/S, R61 E, in Clark County

or \_\_\_\_\_

Water will be used for Domestic Total depth of well 175 ft.

Size of drilled hole 8" to 175 ft. Weight of casing per linear foot 6" = 24 lb.

Thickness of casing 1/4" Temp. of water \_\_\_\_\_

Diameter and length of casing 6" I.D. from 38 ft. to 175 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 89 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Oct. 20, 1955 Date of completion of well Oct. 21, 1955

Type of well rig Bucyrus Erie 24 L, Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
150	155	5	sandstone
155	170	15	sand and gravel water
170	175	5	sandstone water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 155 to 175 ft.

Other aquifers \_\_\_\_\_

First water at \_\_\_\_\_ feet.

Casing perforated

from ~~107~~ 107 to 175 ft.

Size of perforations

3/16" X 10"

