

WELL LOG AND REPORT TO THE STATE  
ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 59789  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Raymond L. Yoss Driller G.R. McKinney & Sons, Inc.  
 Address P.O. Box 171, Pittman, Nevada Address 1042 So. Main St. Lic. No. 45  
 Location of well: SE 1/4 NE 1/4 Sec. 31, T21 N/S, R. 62E, in Clark County  
 or \_\_\_\_\_  
 Water will be used for Domestic Total depth of well 180'  
 Size of drilled hole 12" to 50', 10" to 180' Weight of casing per linear foot 10 gauge  
 Thickness of casing 10 gauge Temp. of water \_\_\_\_\_  
 Diameter and length of casing 8" ID from 0' to 180'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 8'  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well 9/2/61 Date of completion of well 9/12/61  
 Type of well rig Bucyrus Erie 60L

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	soil
3	12	9	clay
12	55	43	sandy clay
55	65	10	white sand(water)
65	70	5	sand stone
70	75	5	sand & little clay
75	80	5	sandy clay & gravel(water)
80	90	10	cement gravel
90	105	15	gravelly clay
105	112	7	gravel with layers of clay
112	130	18	gravel
130	132	2	clay
132	146	14	gravel
146	148	2	clay
148	169	21	gravel
169	170	1	gravelly clay
170	180	10	gravel(water)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 170 to 180 ft.

Other aquifers 55' to 65'

75 to 80'

First water at 55 feet.

Casing perforated  
 from 60' of perf. staggered

Size of perforations

3/16" X 10"

