

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 59806

Rec. 19

Well No. _____

Permit No. _____

Do not fill in

Owner E. R. Stanton Driller S. R. McKinney & Sons, Inc.

Address Las Vegas, Nevada Address 1042 So. Main Lic. No. 45

Location of well: NE 1/4 NE 1/4 Sec. 10., T. 19N/S, R. 60E, in Clark County

Water will be used for Domestic Total depth of well 150'

Size of drilled hole 12" to 50', 10" to 150' Weight of casing per linear foot 10 gauge

Thickness of casing 10 gauge Temp. of water _____

Diameter and length of casing 8" ID from 0' to 150'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 54'

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well 10/18/62 Date of completion of well 10/22/62

Type of well rig Bucyrus Erie 22W

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	5	5	top soil	
5	10	5	gravel	
10	40	30	grey gritty clay	Chief aquifer (water-bearing formation)
40	65	25	brown gritty clay	from <u>105</u> to <u>130</u> ft.
65	68	3	gravel	
68	75	7	brown clay	Other aquifers <u>75 to 78'</u>
75	78	3	gravel (water)	<u>95 to 105'</u>
78	95	17	brown clay	<u>130 to 150'</u>
95	105	10	gravel (water)	
105	130	25	brown clay & gravel streaks (Water)	
130	150	20	brown clay (water)	

First water at 75' feet.

Casing perforated from 71 to 150 ft.

Size of perforations 3/16" X 10"



