

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No.	59906
Rec.	19
Well No.	
Permit No.	

Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Frank Lancaster (Bobbitt) Driller Patrick H. Thompson

Address Las Vegas, Nevada 7155 Ball Dr. Address Las Vegas, Nevada Lic. No. 192

Location of well: SW 1/4 SE 1/4 Sec. 22, T. 19 N/S, R. 60 E, in Clark County

Water will be used for Domestic Total depth of well 605 ft.

Size of drilled hole 12" to 50' 10" to 605' Weight of casing per linear foot L 12#

Thickness of casing 10 gauge Temp. of water cool

Diameter and length of casing 8 5/8" 606 ft. length
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 57 ft.

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well Jan. 18, 1963 Date of completion of well Feb. 12, 1963

Type of well rig Cable tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	Soil
6	15	9	Caliche
15	90	75	Clay
90	98	8	Gravel
98	115	17	Cemented gravel
115	260	145	Clay
260	270	10	Gravel
270	280	10	Clay
280	290	10	Cemented gravel
290	380	90	Clay
380	387	7	Whited Limestone
387	410	23	White clay and gravel
410	495	85	Sticky red clay
495	530	35	Red clay and gravel
530	560	30	Red clay
560	564	4	Gravel
564	594	30	Red clay
594	605	11	Gravel

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)
 from 594 to 605 ft.

Other aquifers 90 - 115

First water at 90 feet.

Casing perforated
 from 90 to 120
540 to 605 ft.

Size of perforations
3/16" X 12" 4 rows

