

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 60066  
 Rec. ....  
 Well No. ....  
 Permit No. ....  
*Do not fill in*

Owner Hugh Armstrong Driller Louis F. Evans

Address 3322 Tonaph Highway, Las Vegas, Nev Address 2020 Carroll N. Las Vegas No. 117

Location of well: N. E 1/4 SW 1/4 Sec 27, T19 N/S, R60 E, in Clark County

Water will be used for domestic Total depth of well 123

Size of drilled hole 50 ft. 12 inch. 73 ft. 10 Weight of casing per linear foot 8" 20 ft. - 11 lbs.  
8" 103 ft. - 28 lbs.

Thickness of casing 8" 20 ft. 10 gauge 8" 103 ft. 1/2 inch wall Temp. of water

Diameter and length of casing 8" I.D. casing 20 ft. 8" I.D. casing 103 ft.  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 66 ft.


If flowing well describe control works (Type and size of valve, etc.)

Date of commencement of well Apr. 9, 1956 Date of completion of well Apr. 16 - 56

Type of well rig Keystone

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	48	48	lime rock
48	52	4	yellow sandy clay
52	63	11	white clay
63	78	15	green sandy clay
78	80	2	green sand (water)
80	84	4	lime rock
84	96	12	yellow sandy clay
96	101	5	lime rock
101	108	7	yellow sticky clay
108	117	9	sand stone (water)
117	123	6	red sticky clay



Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)

from 108 to 117 ft.

Other aquifers 78 to 80

---

First water at 78 feet.

---

Casing perforated

from 60 to 123 ft.

---

Size of perforations

1/2 inch wide 6 inches long

