

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. **60088**

Rec.

Well No.

Permit No.

Do not fill in

Owner Sidney Rominger Driller Nevada Pump & Supply Co.

Address Box 943, Las Vegas, Nevada Address 412 S. 4th, Las Vegas, Nev. L. No. 133

Location of well: NW 1/4 NE 1/4 Sec 27., T.19.N/S, R.60.E, in Clark County

Water will be used for Domestic Total depth of well 120 feet

Size of drilled hole 12' Weight of casing per linear foot 9 lb.

Thickness of casing 12 ga. Temp. of water

Diameter and length of casing 8" x 120 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 63 feet

If flowing well describe control works

(Type and size of valve, etc.)

Date of commencement of well Feb. 11, 1955 Date of completion of well Feb. 12, 1955

Type of well rig Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Top Soil
3	14	11	Caliche
14	54	40	Brown Sandy Clay
54	59	5	Rock
59	69	10	Sticky yellow clay
69	77	8	Sand fine water bearing
77	109	32	Sticky yellow clay
109	117	8	Sand gravel water
117	120	3	Yellow clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 69 to 77 ft.

Other aquifers 109 - 117

First water at 77 feet.

Casing perforated

from 80 to 120 ft.

Size of perforations

1/16" x 6"

