

S X

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. **60349**  
 Rec. **10**  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner John V. Carruth Driller S.R. McKinney & Sons, Inc.

Address Box 498, Pittman, Nevada Address 1042 South Main Lic. No. 45  
 Well Address 5182 N. TIOGA WY.

Location of well: NW  $\frac{1}{4}$  SW  $\frac{1}{4}$  Sec. 34, T. 19N/S, R. 60E, in Clark County

or PARCEL #125-34-310-003

Water will be used for Domestic Total depth of well 252'

Size of drilled hole 12" to 50', 10" to 252' Weight of casing per linear foot 10 gauge

Thickness of casing 10 gauge Temp. of water \_\_\_\_\_

Diameter and length of casing 8" ID from 0' to 252'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 80'

If flowing well describe control works \_\_\_\_\_  
 \_\_\_\_\_ of valve, etc.)

Date of commencement of well 12 \_\_\_\_\_ ion of well 12-15-62

Type of well rig Bucyrus Erie

*2 Houses  
on one  
well  
"D"*

LOG OF

From feet	To feet	Thickness feet
0	3	3
3	15	12
15	31	16
31	45	14
45	52	7
52	60	8
60	65	5
65	95	30
95	98	3
98	115	17
115	185	70
185	220	35
220	242	22
242	244	2
244	250	6
250	251	1
251	252	1

clay  
 gravel (water)  
 clay  
 clay & gravel streaks (water)  
 gravel & clay streaks (water)  
 brown gritty clay (water)  
 gravel (water)  
 clay & gravel streaks  
 gravel (water)  
 clay

Water-bearing Formation, Casing Perforations, Etc.
Chief aquifer (water-bearing formation) from <u>242</u> to <u>244</u> ft.
Other aquifers <u>115 to 185'</u> <u>185 to 220'</u> <u>220 to 242'</u> <u>250 to 251'</u> <u>95 to 98'</u>
First water at <u>95</u> feet.
Casing perforated from <u>120</u> to <u>160</u> ft. <u>180 to 252'</u>
Size of perforations <u>3/16" X 10"</u>



