

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. <b>60387</b>
Rec. <span style="float: right; border: 1px solid black; border-radius: 50%; padding: 5px;">19</span>
Well No. ....
Permit No. ....
<i>Do not fill in</i>

Owner John L. Jeffrey Driller Patrick H. Thompson

Address 1231 Smoketree Ave. L.V. Nev. Address 217 So. 26th St. L.V. Nev. Lic. No. 192

Location of well: SE 1/4 SW 1/4 Sec 34, T19 N/S, R60 E, in Clark County

or .....

Water will be used for Domestic Total depth of well 200'

Size of drilled hole 2" to 50' - 10" - 50' to 200' Weight of casing per linear foot 28#

Thickness of casing .315 Temp. of water .....

Diameter and length of casing 8" dia. - 201' length  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface 51'

If flowing well describe control works .....

(Type and size of valve, etc.)

Date of commencement of well Sept. 11, 1958 Date of completion of well Sept. 16, 1958

Type of well rig Cable Tools

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	8	8	sandy soil	
8	12	4	caliche	
12	35	23	white clay	
35	62	27	cemented gravel	
62	78	16	grey sandy clay	
78	87	9	sand and gravel	
87	100	23	cemented gravel	
100	144	44	brown clay	
144	187	43	sandy brown clay	
187	200	13	gravel	
				Chief aquifer (water-bearing formation)
				from <u>187</u> to <u>200</u> ft.
				Other aquifers <u>78 - 87</u>
				First water at <u>78</u> feet.
				Casing perforated
				from <u>120</u> to <u>200</u> ft.
				Size of perforations
				<u>3/16x12 - 4 rows</u>



