


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. **60517**  
 Rec.....  
 Well No.....  
 Permit No.....



*Do not fill in*

Owner Betty Wilson Driller S.R. Mc Kinney & Son

Address Las Vegas, Nevada Address 1042 So. Main St. L.V. Lic. No. 45

Location of well: SW 1/4 Sec. 34 T. 19 N/S, R. 60 E, in Clark County

or.....

Water will be used for Domestic Total depth of well 191ft.

Size of drilled hole 12" to 50ft., 10" to 191ft. Weight of casing per linear foot 10 Gauge

Thickness of casing 8" ID 10 Gauge Temp. of water.....

Diameter and length of casing 8" ID 0ft. to 191ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface 90 ft.

If flowing well describe control works.....  
(Type and size of valve, etc.)

Date of commencement of well 6/9/57 Date of completion of well 6/13/57

Type of well rig Bucyrus Erie 24L Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	20	20	Cement gravel
20	23	3	Clay
23	42	19	Cement gravel
42	45	3	Clay
45	60	15	Cement gravel
60	90	30	Clay
90	108	18	Cement gravel
108	115	7	White Clay
115	120	5	White clay & gravel
120	122	2	Clay
122	136	14	Cement gravel
136	145	9	Clay
145	170	15	Cement gravel & sand (Water)
170	175	5	Cement gravel & sand
175	178	3	Clay
178	191	13	Cement gravel (Water)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 178 to 191 ft.

Other aquifers 145-170 ft.

115-120 ft.

First water at 115 feet.

Casing perforated

from 151 to 191 ft.

Size of perforations

3/16x 10"



